



# CAMATHICK CME CONS.



## Synthetic Thickener for Pigment Printing

### SALIENT FEATURES

- ▶ Generates high viscosity at low dosages
- ▶ Easy to disperse due to low viscosity
- ▶ Gives smooth swelling & homogeneous blend
- ▶ Have Optimum rheology to give sharp line definition in prints
- ▶ No clogging of screens even in finer mesh & high speed
- ▶ Excellent brightness, levelness & depths of prints
- ▶ APEO / NPEO free, Eco – friendly
- ▶ Can be pumped

### CHARACTERISTICS

Appearance	: Off – white to pale yellow pourable liquid
Chemical Nature	: Polymeric compound
Ionic Nature	: Anionic
Dispersibility	: Excellent with water in all proportions
pH	: 7 ± 0.5
Compatibility	: Excellent with anionic & nonionic products

### APPLICATION

Substrate	: Cellulosic, polyester fabric & their blends
Machines	: Printing equipments & machines
Function	: Thickener in pigment printing
Guide Recipes	: <b>Preparation of Stock Paste-</b>

<b>CAMATHICK CME CONS.</b>	<b>1.5 – 1.7 parts</b>
CAMAMICRO ECO Super	6.0 – 12 parts
PRINTOSOFT CS 40	1 – 2 parts
Water.....To bulk up to 100 parts	

#### **Preparation of Print Paste-**

CAMEX - Pigment Emulsion	x parts
CAMAFIX CCL (add just before printing)	1 part
Stock paste.....To bulk up to 100 parts	

Print – Dry – Cure at 150° C for about 3 – 5 minutes.

### SPECIAL REMARKS

Storage Stability	: Minimum 6 months under standard conditions of storage. Avoid heat, sunlight & moisture.
Container	: 60 kg & 120 kg HDPE barrels

Disclaimer: All recommendations for the use of our products, whether given by us in writing, orally or to be implied from the results of trials, are based on our present state of knowledge & experience. Owing to the variation in local application conditions, they cannot be claimed to be complete. Hence, we cannot accept any responsibility thereof. All claims, liabilities – also with a view to claim of third parties – are excluded. It is advised to conduct lab & bulk trials before using in bulk production.