



CAMEX HOUSE, 2nd Floor, Stadium - Commerce
Road, Navrangpura, AHMEDABAD-380 009 (INDIA)



PHONE : +91-79 26462260, 26462262
F A X : + 9 1 - 7 9 - 2 6 4 6 2 1 2 3



WEB : www.camexltd.com
E-MAIL: info@camex.co.in

Product Data Sheet

LEAD STEARATE – PREMIUM

PARAMETERS	SPECIFICATIONS
Metal (%)	28-30
Ash Content	30-32
Loss on drying (%)	0.5 Max
FFA (%)	1.0 Max
Bulk Density (g/l)	400-450
Melting Point (°C)	110-112
Particle Size	Min 97% through 240 mesh screen
Physical Form	Fine Powder

DESCRIPTION

LEAD STEARATE PREMIUM is a derivative of Stearic Acid and lead mono oxide. It is excellent stabilizer for both rigid & flexible PVC. It also acts a lubricant and dispersion agent.

SOLUBILITY

LEAD STEARATE PREMIUM is insoluble in water and alcohol, ether, but soluble in benzene, acids or common solvents when hot.

SUGGESTED APPLICATIONS

Lead Stearate is used as heat stabilizer and lubricant in all rigid and flexible PVC applications as it promotes fusion.

STORAGE

LEAD STEARATE PREMIUM has long storage life if kept cool & dry
Indoor storage is recommended. Store in cool, dry, ventilated place
Keep away from heat and sources of ignition. Do not breathe dust.
Avoid contact with eyes.

PACKING

25 KG HDPE BAG

SAFETY & ENVIRONMENTAL INFORMATION

Avoid contact with skin, eyes and clothing: may cause irritation. Wear protective safety glasses. Use personal protective equipment. Ensure adequate ventilation. Avoid dust formation. Remove all sources of ignition. Do not breathe vapors/dust. do not allow material to contaminate ground water system. Do not let product enter drains.