



CAMEX HOUSE, 2nd Floor, Stadium - Commerce
Road, Navrangpura, AHMEDABAD-380 009 (INDIA)



PHONE : +91-79 26462260, 26462262
F A X : + 9 1 - 7 9 - 2 6 4 6 2 1 2 3



WEB : www.camexltd.com
E-MAIL: info@camex.co.in

Product Data Sheet

PVC STABILIZER: GRADE 4032

Product Description:

It is a homogenous mixture of metallic stearates, waxes, basic lead stabilizers and antioxidants produced by In-situ method, it avoids weighing and mixing of individual stabilizers which reduces the weighing error and too much inventory of various stabilizers & lubricants. One bag type production, easy and convenient It has a good balance of internal and external lubrication.

Chemical Composition:

Homogeneous mixture of metallic stearates, lead stabilizer, waxes & antioxidants

Technical Specification:

Appearance	:	Off White Flakes/ white powder
Bulk Density	:	400-550 g/l
Dropping Point	:	90-110°C
Free fatty Acid	:	1.0% max
Volatile Matter	:	0.5% max
Lead Content (PbO%)	:	30 – 32 %

Application:

Specially designed for PVC profiles/ doors /window and Pipe Adequate lubrication with antioxidant

STORAGE

ONE PACK STABILIZER has long storage life if kept cool and dry. Indoor storage is recommended, Store in cool, dry, ventilated place. Keep away from heat and sources of ignition. Do not breathe dust. Avoid contact with eyes.

PACKING

ONE PACK STABILIZER is available in 25 kgs HDPE Bag

SAFETY & ENVIRONMENTAL INFORMATION

Avoid contact with skin, eyes and clothing: may cause irritation. Wear protective safety glasses. Use personal protective equipment. Ensure adequate ventilation. Avoid dust formation. Remove all sources of ignition. Do not breathe vapors/dust. do not allow material to contaminate ground water system. Do not let product enter drains.