



PRINTOSOFT CS40

Speciality Softener for Pigment Printing

SALIENT FEATURES

- ▶ Imparts excellent smoothness & suppleness to prints
- ▶ No interference on yield, & sharpness of prints
- ▶ No adverse affect on rheology of print paste
- ▶ Enhances brightness & handle of prints
- ▶ High resistance to mechanical shear
- ▶ Excellent thermal stability
- ▶ APEO / NPEO free

CHARACTERISTICS

Appearance	: Off - white paste
Chemical Nature	: Polyoxyethoxylated derivative
Ionic Nature	: Nonionic
Miscibility	: Easily miscible in print paste formulations
pH	: 7 ± 0.5
Compatibility	: Excellent with the ingredients of pigment print recipes

APPLICATION

Substrate	: Cellulosic, polyester fabric & their blends
Machines	: Printing equipments & machines
Function	: Softening in pigment printing
Guide Recipes	: 1 – 2 % in organic or inorganic pigment print paste formulations

SPECIAL REMARKS

Storage Stability	: Minimum 6 months under normal conditions of storage
Container	: 50 & 200 kg Carbuoys & barrels

Disclaimer: All recommendations for the use of our products, whether given by us in writing, orally or to be implied from the results of trials, are based on our present state of knowledge & experience. Owing to the variation in local application conditions, they can not be claimed to be complete. Hence, we can not accept any responsibility thereof. All claims, liabilities – also with a view to claim of third parties – are excluded. It is advised to conduct lab & bulk trials before using in bulk production.